

ADDI-PROX® SC/F

ADDI-PROX® SC/F is an all-purpose system cleaner that is used in systems operating with cutting fluids. This cleaning agent should be used before the systems are filled with new water miscible cutting fluids. All factors that can damage cutting fluids such as oil residues, debris, bacteria, fungi or any other dirt will be removed, i.e. cleaned away from the system. ADDI-PROX® SC/F ensures optimal conditions for a new set up of the cutting fluid.

FEATURES / BENEFITS:

- Compatible with all cutting fluid systems (stand-alone machines or central system)
- Its high washing and flushing action ensures cleaner machines
- Disinfection of the system
- Cleans out all kinds of residues
- Excellent compatibility
- Easy-to-use
- Is to be removed together with the old cutting fluid

DATA OF THE CONCENTRATE:

Determination	Method	Unit	Value
Density, 20 °C	DIN 51 757	[kg/m ³]	1054
Kin. viscosity, 40 °C	DIN 53 018	[mm ² /s]	2.0
Refractive index, n _D ²⁰	DIN 51 423	---	1.375

Recommended Concentration (depending on process and material):

1.0 – 2.0 %

ADDI-PROX® SC/F is to be added directly to the cutting fluid and must remain min. 8 hours in the system, if possible when it is running.

Use biocides safely. Before use, always read the characterization and the product information.

Shelf Life / Storage Condition:

6 month stored between +10 °C (50 °F) and +30 °C (86 °F)

Industrial Health and Safety - Environmental Protection:

Complies with German TRGS 611 (Prevention of Nitrosamine formation).

Is labelled – **C corrosive** – under the European Directive for Classification, Packaging and Labelling of Dangerous Preparations.